

Light quality:


CRI: 92,9

Color temperature:

2738 K

Output: 705 lm  
Peak: 21732 cd

Power: 13,0 W  
237V @ 0,055A




Product name:  
**turn plus 10deg 13W 2700K**

Date and time:  
**5-1-2017 13:10:17**

Beam angle

**9,2°**






Color



CIE1931  
x: 0,456  
y: 0,408


Spectra






COLOR

TM30: 90,0



CRI: 92,9 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93,99	94,94	93,60	93,90	92,87	93,34	94,00	86,58	68,46	86,44	94,23	82,39	94,11	95,33	91,12


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
91,48	91,96	85,97	89,12	90,72	89,77	88,47	92,25	93,23	92,28	87,43	88,05	91,72	89,11	89,86	87,51

CQS Q values


Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
89,47	96,67	88,18	89,14	88,49	85,31	84,81	90,62	95,66	90,15	90,37	90,66	91,52	88,84	88,89

CQS: 89,4



## Color parameters

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Duv
2738 K	92,9	68,5	90,0	102,3	89,4	0,5	0,4	0,3	0,4	0,0006



### Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
21,7K	21,3K	19,9K	17,1K	13,3K	9,3K	6,2K	3,9K	2,5K	1,7K	1,2K	0,8K	0,6K	0,4K	0,3K	0,2K	0,1K	0,0K	0,0K	0,0K
100%	98%	91%	79%	61%	43%	28%	18%	11%	8%	5%	4%	3%	2%	1%	1%	0%	0%	0%	0%

### Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
21,7K	21,3K	19,9K	17,1K	13,3K	9,3K	6,2K	3,9K	2,5K	1,7K	1,2K	0,8K	0,6K	0,4K	0,3K	0,2K	0,1K	0,0K	0,0K	0,0K
100%	98%	91%	79%	61%	43%	28%	18%	11%	8%	5%	4%	3%	2%	1%	1%	0%	0%	0%	0%

### Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
21,7K	21,3K	19,9K	17,1K	13,3K	9,3K	6,2K	4,1K	2,8K	2,0K	1,5K	1,2K	0,9K	0,6K	0,4K	0,3K	0,2K	0,1K	0,0K	0,0K
100%	98%	91%	78%	61%	43%	28%	19%	13%	9%	7%	5%	4%	3%	2%	1%	1%	0%	0%	0%

### Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
21,7K	21,3K	19,9K	17,1K	13,3K	9,3K	6,2K	4,1K	2,8K	2,0K	1,5K	1,2K	0,9K	0,6K	0,4K	0,3K	0,2K	0,1K	0,0K	0,0K
100%	98%	91%	78%	61%	43%	28%	19%	13%	9%	7%	5%	4%	3%	2%	1%	1%	0%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
9,2°	17,1°	25,6°	99,7%	99,7%