

°ledline

Continuous lines of light, without limits.
Each led module can be cut every 8 cm, this
gives architects and lighting designers a lot of
flexibility.

Led line has a very good efficiency. A high-tech
diffusor was implemented to block as little light
as possible and still give an opal look.

°ledline 25

material aluminum
weight 0,8 kg/m - 0,52 lb/ft
voltage 24Vdc
cri >90
wattage 13 or 28W / meter
dali supported DT6 option



IP20   

LL25.L.B.T.K		led modules cuttable every 8 cm
Length	2000	standard length
	100 - ...	custom length (multiple of 8 cm)
Body color	BK	black matt ral 9011
	WH	white matt ral 9016
	AL	aluminum color ral 9006 (on request only)
Type	SM	surface mount
	PD	pendant
K	WW.13	2700K 13W 960 lm/m
	WW2.13	3000K 13W 1020 lm/m
	NW2.13	4000K 13W 1020 lm/m
	WW.28	2700K 28W 1650 lm/m
	WW2.28	3000K 28W 1780 lm/m
	NW2.28	4000K 28W 1850 lm/m
Accessories	LL25.EC.BK	led line 25 End Cap Black
	LL25.EC.WH	led line 25 End Cap White
	LL25.EC.AL	led line 25 End Cap Aluminum
Driver		24Vdc power supply (remote)

